

STEALTH FIGHTER

FOLD N' FLY DIRECTIONS

1. Each picture box corresponds with each step number on jet. Start with picture box 1 and fold line 1 on the jet etc.

2. TAPE. Tape should be applied neatly in the boxed areas.

3. CUTTING: Cut only red lines or blue areas in their order.

4. FOLDS: Make all folds accurately on the lines as marked, do not go beyond their mark and crease each fold well.



With printed side down, fold dashed line 1 over onto plane as shown. This fold must be firmly creased.



Fold dashed line 2 over onto plane as shown. This fold is done in the same way fold 1 was done. This fold must be firmly creased.



Fold dashed line 3 over onto plane as shown. This fold is done in the same way fold 2 was done. This fold must be firmly creased.



With printed side down, cut on red line 4. Do not cut beyond the line.



Fold dashed line 5 onto blank side. Apply tape to areas marked 5T.



Cut out light blue area 6C away from plane.



Fold dashed line 7 (white area) downward making sure dotted line 7 (down the middle) is creased all the way past the tail. Make sure the folds meet in the cockpit.



Crease the folds well.

Fold white dashed line 7 (on fuselage) down as shown. Crease the folds well.



Fold wings upward on white dotted line 7 found where wing meets fuselage.



Fold dotted line 8 upward as shown. This fold sticks up from the center. This step can be made easier by first folding dotted line 8 DOWN, just as fold 7, then reversing the fold UP and opposite of fold 7.



Crease folds well.


With printed side down, fold dashed lines 9 over onto bottom of plane. Crease these folds well.




Push the wing sections together towards the middle (like an accordion) and tape in places marked 10T. Near the cockpit and at the tail section. To insure a good fold, re-crease lines 7&8 in the center white area.




On bottom of plane, apply tape to places marked 11T.




Cut out the tail sections. Fold each tail in half and tape its back edge. Fold lower piece up against the side which has writing. Crease the fold well.



Apply tape to bottom "flap" of tail and tape onto place marked "TAIL HERE". Make sure the tails are aligned with center seam.



Bend tails up approx. 45 degrees. To ready your plane for flight, look directly at the rear to check that the wings and tails are balanced (equal in angle) and as straight as possible.



FLIGHT TUNING YOUR PLANE

Test fly with an easy, level toss, holding the plane by the small "spine" under tail section.



If plane dives right, bend the back edge of the left wing or tail up slightly.

If the plane dives left, bend the back edge of the right wing or tail up slightly.

DO NOT TOSS YOUR PLANE WHEN PEOPLE ARE IN THE AREA.



AG Industries Inc., Redmond, WA (425) 885-4599
© Michael Lee 1996, 1998